

## Technical Data Sheet U Series

### Basic info

KSF U 60x865-111    KSF U 60x730-111

**Nominal length (mm)**

865                                      730

**tube diameter (mm)**

60    60

**Weight (kg)**

3.10                                        2.70

**Item number**

21035                                      21033

### Construction

- Coating: Hot-dip galvanized according to DIN EN ISO 1461
- Continuous welded helix
- Patented conical body forged from a single piece of tubing

### Applications



### Accessories



**Screwing bar short**

0.60 kg

Item No. 20070



KSF U 60x730-111

## Technical Data

### KSF U 60x865-111    KSF U 60x730-111

<b>a</b>	<b>Length (mm)</b>	865	730
<b>b</b>	<b>Shaft outer diameter (mm)</b>	60	60
<b>c</b>	<b>Square hole spacing (mm)</b>	42	42
<b>d</b>	<b>Middle square hole spacing (mm)</b>	94	94
<b>e</b>	<b>Square hole spacing (mm)</b>	50	50
<b>f</b>	<b>Square hole diameter* (mm)</b>	11	11
<b>g</b>	<b>Gauge (mm)</b>	111	111
<b>h</b>	<b>U profile width (mm)</b>	70	70
<b>i</b>	<b>U profile depth (mm)</b>	134	134

\* to fit M10 carriage bolts

